



APPLICATION NOTE 347

## Converting the DS2151/DS2153 Demo Kits

*Abstract: The DS2151DK and DS2153DK are ordered and shipped for either T1 or E1 operation. However, the kits are easily converted to operate on the other mode. This application note describes how to convert the demo kits to either T1 or E1 operation.*

The DS2151DK & DS2153DK are ordered and shipped for either T1 or E1 operation. However, the kits are easily converted to the other mode.

To convert from DS2151DK to DS2153DK: T1→

1. Place DS2153 in location marked U1.
2. Place 2.048 MHz oscillator in location marked X3.
3. Place 8.192 MHz crystal in location marked X1.
4. Remove and replace Rr.
5. Place Rt as required, see **note 3** below.

To convert from DS2153DK to DS2151DK: E1→

1. Place DS2151 in location marked U1.
2. Place 1.544 MHz oscillator in location marked X3.
3. Place 6.176 MHz crystal in location marked X1.
4. Remove and replace Rr.
5. Place Rt as required, **note 3** below.

The table below details the required components.

Component	Description	T1	E1
U2	SCT	DS2152	DS2154
X1	PULLABLE CRYSTAL <sup>1</sup>	6.176 MHz	8.192 MHz
X3	OSCILLATOR <sup>1</sup>	1.544 MHz	2.048 MHz
R5 & R6	Rt	0 <sup>2,3</sup>	8.2 <sup>2</sup>
R7 & R8	Rr	50	37.5 for Ohm Termination 60 for 120 Ohm Termination

### Notes:

1. Recommended oscillators: NTH039A-1.544000 & NTH039A-2.04800.  
Recommended crystals: 6.176 MHz SRX5310(L) & 8.192 MHz SRX5469(L)

Saronix  
151 Laura Lane  
Palo Alto, CA 94303  
Phone: (415) 856-6900

Fax: (415) 856-4732  
<http://www.saronix.com>

2. The DS2151DK and DS2153DK are both shipped with a 1:1.15 transformer (PE-65388) in the transmit path. Some of the configurations in the data sheets specify a 1:1.36 transformer, PE-64937 is a 1:1.36 transformer available from Pulse Engineering.

Pulse Engineering  
P.O. Box 12236  
San Diego, CA 92112  
Phone: (619) 674-8100  
Fax: (619) 674-8262  
<http://www.pulseeng.com>

3. The DS2151DK and DS2153DK are both shipped with  $R_t = 0$  , R5 & R6 are shorted in the PCB. Some of the configurations in the data sheets specify non zero resistors for  $R_t$ . In order to place resistors,  $R_t \neq 0$ , the traces must be cut. Carefully cut the traces connecting the through holes for R5 & R6 with an X-acto knife, and solder the resistors in place.

---

Application Note 347: <http://www.maxim-ic.com/an347>

### **More Information**

For technical questions and support: <http://www.maxim-ic.com/support>

For samples: <http://www.maxim-ic.com/samples>

Other questions and comments: <http://www.maxim-ic.com/contact>

AN347, AN 347, APP347, Appnote347, Appnote 347

Copyright © by Maxim Integrated Products

Additional legal notices: <http://www.maxim-ic.com/legal>